


STINGER XL RGB70,000 (Total Power 72,000mW) 50W up to 140W available

chaining, built in controller for input, playback, size, color and more.





What's New! IP65 Rated outdoor weatherproof enclosure.

Specifications Light Source

Red: 24000mW @ 638nm Semiconductor diodes Green: 24000mW @ 520nm Semiconductor diodes Blue: 24000mW @ 445nm Semiconductor diodes Total Output @ Projector window: 72,000mW Beam Diameter (Projector Window): < 13*16 mm Divergence (Full angle): < 0.95mrad (Full angle) Modulation: Analog 100KHZ Laser Class: Class IV

Scanner

Galvo: 20K @8° Scan Angle: 40° Max

Thermal Control

Cooling: TEC Peltier Elements Ventilation: 70mm Low noise fan * 3

Interfaces & Controls

Control: ILDA, Auto, SD-Card, DMX in / Out Optional FB4 ready Safety: Key Switch, Scan-Fail-Safe Switch, Interlocks, E-Stop Scan Image Invert: Invert – X, Invert – Y Color adjustment: Intensity R, G, B (0-100%) Mains: Neutrik PowerCON®

Electric

Operating Voltage: AC 110V-240V 50-60Hz Power Consumption: 1200W Max

Physical

L * W * H: 581mm * 780mm * 467mm

Weight: 75.00kg IP grade: IP65

Stinger Lasers www.stingerlasers.com 1-(212)629-7109 info@laserencore.com

Laser Light Show System Sales, Rentals, Installations - Nationwide / Worldwide